

**Fort Monmouth Morale, Welfare and Recreation Delivery System
Playground Checklist**

Playground Charleswood Pavilion

Date & Time 9 May 2003 0800

- | | Hazards | | Maintenance | Comments |
|--|--------------------------------------|---|------------------------------------|----------|
| 1. Surfaces under playground equipment meet the Consumer Product Safety Commission's Impact attenuation requirement of 200g peak acceleration. | Y <input checked="" type="radio"/> N | Y | <input checked="" type="radio"/> N | _____ |
| 2. Loose materials e.g. shredded bark, sand, or pea gravel, used to satisfy this requirement is maintained to a uniform thickness of six inches or more, depending upon the Consumer Product Safety Commission's thickness requirement. Artificial turfs do not require 6 inch thickness. | Y <input checked="" type="radio"/> N | Y | <input checked="" type="radio"/> N | _____ |
| 3. Existing concrete, asphalt, or similar surfaces adjacent to or beneath stationary play equipment are covered with a resilient molded rubber mat safety surface meeting the attenuation requirement of not more than 200g peak acceleration. | Y <input checked="" type="radio"/> N | Y | <input checked="" type="radio"/> N | _____ |
| 4. Materials retain shock absorbing value year around under local conditions or equipment is taken out of service if playing surface becomes unsuitable, e.g., removal of swings if winter season causes a hard freeze. Soft turf, sand and grass are not acceptable when compacted or frozen. | Y <input checked="" type="radio"/> N | Y | <input checked="" type="radio"/> N | _____ |



**Fort Monmouth Morale, Welfare and Recreation Delivery System
Playground Checklist**

Playground Charleswood Pavilion

Date & Time 11 April 2003 1100

- | | Hazards | | Maintenance | Comments |
|--|--------------------------------------|---|------------------------------------|----------|
| 1. Surfaces under playground equipment meet the Consumer Product Safety Commission's Impact attenuation requirement of 200g peak acceleration. | Y <input checked="" type="radio"/> N | Y | <input checked="" type="radio"/> N | _____ |
| 2. Loose materials e.g. shredded bark, sand, or pea gravel, used to satisfy this requirement is maintained to a uniform thickness of six inches or more, depending upon the Consumer Product Safety Commission's thickness requirement. Artificial turfs do not require 6 inch thickness. | Y <input checked="" type="radio"/> N | Y | <input checked="" type="radio"/> N | _____ |
| 3. Existing concrete, asphalt, or similar surfaces adjacent to or beneath stationary play equipment are covered with a resilient molded rubber mat safety surface meeting the attenuation requirement of not more than 200g peak acceleration. | Y <input checked="" type="radio"/> N | Y | <input checked="" type="radio"/> N | _____ |
| 4. Materials retain shock absorbing value year around under local conditions or equipment is taken out of service if playing surface becomes unsuitable, e.g., removal of swings if winter season causes a hard freeze. Soft turf, sand and grass are not acceptable when compacted or frozen. | Y <input checked="" type="radio"/> N | Y | <input checked="" type="radio"/> N | _____ |

Signature

**Fort Monmouth Morale, Welfare and Recreation Delivery System
Playground Checklist**

Playground Chickwood Pavilion

Date & Time 14 March 2003 0930

- | | Hazards | | Maintenance | Comments |
|--|--------------------------------------|---|------------------------------------|----------|
| 1. Surfaces under playground equipment meet the Consumer Product Safety Commission's Impact attenuation requirement of 200g peak acceleration. | Y <input checked="" type="radio"/> N | Y | <input checked="" type="radio"/> N | _____ |
| 2. Loose materials e.g. shredded bark, sand, or pea gravel, used to satisfy this requirement is maintained to a uniform thickness of six inches or more, depending upon the Consumer Product Safety Commission's thickness requirement. Artificial turfs do not require 6 inch thickness. | Y <input checked="" type="radio"/> N | Y | <input checked="" type="radio"/> N | _____ |
| 3. Existing concrete, asphalt, or similar surfaces adjacent to or beneath stationary play equipment are covered with a resilient molded rubber mat safety surface meeting the attenuation requirement of not more than 200g peak acceleration. | Y <input checked="" type="radio"/> N | Y | <input checked="" type="radio"/> N | _____ |
| 4. Materials retain shock absorbing value year around under local conditions or equipment is taken out of service if playing surface becomes unsuitable, e.g., removal of swings if winter season causes a hard freeze. Soft turf, sand and grass are not acceptable when compacted or frozen. | Y <input checked="" type="radio"/> N | Y | <input checked="" type="radio"/> N | _____ |

[Handwritten signature]

[Handwritten signature]